

WAAS

CH **45611**

W04A

APP CRS

044°

Rwy Idg

8001

TDZE

535

Apt Elev

559

RNAV (GPS) RWY 4

FREDERICK DOUGLASS/GREATER ROCHESTER INTL (ROC)

RNP APCH - GPS.

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. For inop ALS, increase LNAV Cats C/D visibility to 1 1/2 SM.

▲

ALS-F-2

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct BILAW and hold.

ATIS 124.825	ROCHESTER APP CON 119.55 269.6	ROCHESTER TOWER 118.3 254.3	GND CON 121.7	CLNC DEL 118.8 343.65
------------------------	--	---------------------------------------	-------------------------	---------------------------------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).				
CATEGORY	A	B	C	D
LPV DA		735/18	200 (200-1/2)	
LNAV/VNAV DA		1290-2 1/4	755 (800-2 1/4)	
LNAV MDA	1200/24	665 (700-1/2)	1200-1 1/2	665 (700-1 1/2)
CIRCLING	1200-1	641 (700-1)	1500-2 3/4 941 (1000-2 3/4)	1500-3 941 (1000-3)

ELEV 559

D TDZE 535

ROCHESTER, NEW YORK

Amdt 2C 31OCT24

FREDERICK DOUGLASS/GREATER ROCHESTER INTL (ROC)

43°07'N-77°40'W

RNAV (GPS) RWY 4