SC-3, 04 SEP 2025 to 02 OCT 2025

ALAMO FIVE DEPARTURE RADAR required. SAN ANTONIO DEP CON **TOP ALTITUDE:** 125.7 290.225 **ASSIGNED BY ATC** ATIS 128.8 CLNC DEL (When twr closed) 121.7 **GND CON** 121.7 379.9 STINSON TOWER * 118.2 (CTAF) 379.9 **COWBOY** 116.2 CVE ::= Chan 109 BROWNWOOD 113.55 BWD -: **JUMBO** Chan 82(Y) GOOCH SPRINGS 112.5 AGJ Chan 72 FL180 3200 359° (86) **CENTEX** 112.8 CWK ==== STONEWALL Chan 75 113.8 STV **∷**. Chan 85 **HENLY** NOTE: GOBBY Transition: Right turn at GOBBY NA for aircraft required FL240 and above. NOTE: HENLY Transition: Right turn at HENLY NA **GOBBY** for aircraft required FL240 and above. SAT 25 My TAKEOFF MINIMUMS Rwy 10: Standard with minimum climb of 4100 3300 230'/NM to 1900. Rwy 14: Standard with minimum climb of 220'/NM to 1900. SAN ANTONIO Rwy 28: 300-15% or standard with minimum 116.8 SAT 🗀 climb of 230'/NM to 900, or Chan 115 alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1800' prior to DER. Rwy 32: Standard with minimum climb of 230'/NM to 1700. (CONTINUED ON FOLLOWING PAGE) NOTE: Chart not to scale.