

LOC/DME I-RMT

110.35

Chan 40 (Y)

APP CRS

126°

Rwy Ldg

8279

TDZE

3963

Apt Elev

3967

SCOTTSBLUFF/WESTERN NEBRASKA RGNL/WM B HEILIG FLD (BFF)

ILS or LOC/DME RWY 12

⚠

When local altimeter setting not received, use Alliance altimeter setting and increase DA 91 feet; all MDAs 100 feet, and S-LOC 12 and Circling Cat B/C/D visibilities ¼ mile. For inoperative MALSR, when using Alliance altimeter setting, increase S-ILS 12 visibility to 1. VDP NA when using Alliance altimeter setting.

MALSR

MISSED APPROACH: Climb to 4500 then climbing left turn to 6900 direct BFF VORTAC and hold, continue climb-in-hold to 6900.

ASOS 121.025	DENVER CENTER 127.95 338.2	UNICOM 123.0 (CTAF) 0
-----------------	-------------------------------	--------------------------

Diagram details: Approach path starts at 6900 NoPT (126°/4.5), passes (IAF) WHARF (I-RMT 17.3), (IF/IAF) LEDSE (I-RMT 12.8), CAPGA (I-RMT 6.7), and FERPO (I-RMT 1.8). Altitudes: 5700, 5000, 4500. Distances: 1.1, 1.6, 1.1, 1.7, 0.3 NM. Localizer: 110.35, I-RMT 1.8, Chan 40(Y). Missed approach: Climb to 4500, then 6900, then 111.8 AIA (R-242, Chan 55). Alternate missed approach: 062° to 242°.

ELEV 3967	D	TDZE 3963
-----------	---	-----------

Diagram details: HIRL RWY 12-30 (126°), MIRL RWY 5-23 (304°). Distances: 8002 X 150, 8279 X 150.

DME REQUIRED

ILS unusable from FERPO/1.8 DME inbound.				
One Minute Holding Pattern				
LEDSE I-RMT 12.8				
CAPGA I-RMT 6.7				
6900 ← 306° 126° → 5700				
GS 3.00° TCH 57				
6.1 NM 3.2 NM 1.7 NM 0.3				
CATEGORY	A	B	C	D
S-ILS 12	4163-½ 200 (200-½)			
S-LOC 12	4640-½ 677 (700-½)		4640-1½ 677 (700-1½)	4640-1¾ 677 (700-1¾)
CIRCLING	4640-1 673 (700-1)		4640-2 673 (700-2)	4740-2½ 773 (800-2½)

SCOTTSBLUFF, NEBRASKA

SCOTTSBLUFF/WESTERN NEBRASKA RGNL/WM B HEILIG FLD (BFF)

Orig-B 30JAN20

41°52'N-103°36'W

ILS or LOC/DME RWY 12