

TACAN RWY 21L

TACAN SUU Chan 113	APCH CRS 213°	Rwy Idg 10,995 TDZE 58 Arprt Elev 63	[USAF]	TRAVIS AFB (KSUU)
------------------------------	-------------------------	---	--------	-------------------

*** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile, CAT CDE vis to 1½ miles.**
**** Circling not authorized NW of Rwy 3L-21R.**

ATIS 135.55 292.125	APP CON 119.9 322.325 (S) 126.6 281.45 (N)	TOWER 120.75 254.4	GND CON 121.8 289.4	CLNC DEL 127.55 335.8
--------------------------------------	---	-------------------------------------	--------------------------------------	--

When circling to Rwy 3L at night, operational VGSI required, remain at or above VGSI glidepath until threshold.

Knots	60	120	180	240	300	360
V/V(fpm)	240	480	720	960	1200	1440

ATC Climb of 240 ft/NM to 5000

EMERG SAFE ALT 100 NM 12,600

2300	5000	SUU R-343	BTRY SUU 13	VGSI and descent angles not coincident (VGSI Angle 2.80/TCH 75).
------	------	-----------	-------------	--

ELEV 63	TDZE 58
----------------	----------------

CATEGORY	A	B	C	D	E
S-21L*	500/24 442 (500-½)		500/45 442 (500-¾)		
CIRCLING**	560-1 497 (500-1)	660-1 597 (600-1)	840-2¼ 777 (800-2¼)	1200-3 1137 (1200-3)	

HIRL Rwy 3R-21L
MIRL Rwy 032° - 212°
TDZL/CL Rwy 3R, 21L