

LOC/DME I-FMN	APP CRS	Rwy Ldg	6248
111.9	256°	TDZE	5507
Chan 56		Apt Elev	5507


ILS or LOC RWY 25
FOUR CORNERS RGNL (FMN)

DME required.


⚠ VDP N/A with Durango altimeter setting. Circling N/A for Cat D southeast of Rwy 5 and south of Rwy 25. When local altimeter setting not received, use Durango altimeter setting and increase S-ILS 25 DA to 5950 feet and all visibilities ½ SM; increase all MDAs 260 feet and S-LOC 25 visibility Cat C/D ¾ SM, and Circling visibility Cat B ¼ SM and Cat C ½ SM.

MISSED APPROACH: Climb to 6100 then climbing right turn to 9000 on heading 321° and on RSK VORTAC R-280 to FLUME INT and hold, continue climb-in-hold to 9000.


ATIS 127.15	DENVER CENTER 118.575 348.7	FARMINGTON TOWER★ 118.9 (CTAF) 257.8	GND CON 121.7	UNICOM 122.95
----------------	--------------------------------	---	------------------	------------------



ELEV 5507	D	TDZE 5507
-----------	---	-----------



REIL Rwy 23 and 25	1
MIRL Rwy 5-23 and 7-25	1
FAF to MAP	7 NM
Knots	60 90 120 150 180
Min:Sec	7:00 4:40 3:30 2:48 2:20



6100

↑

9000

hdg 321°

RSK

R-280

FLUME

△

RSK VORTAC

Remain within 10 NM

076°

8300

256°

7800

7800

GS 3.00°

TCH 56

Use I-FMN DME when on the localizer course.

EPOTE I-FMN 8.1

KODYS I-FMN 4.5

I-FMN 2.1

I-FMN 1.1

6640

7800

7800

8300

1 NM

2.4 NM

3.6 NM

CATEGORY	A	B	C	D
S-ILS 25	5707-¾ 200 (200-¾)			
S-LOC 25	5880-1 373 (400-1)			
CIRCLING	6020-1 513 (600-1)	6140-1 633 (700-1)	6380-2½ 873 (900-2½)	6400-3 893 (900-3)