

WAAS CH 45613 W23A	APP CRS 234°	Rwy Ldg TDZE Apt Elev	10000 409 435
--	------------------------	-----------------------------	--

RNAV (GPS) Y RWY 23R

RALEIGH-DURHAM INTL (RDU)



RNP APCH - GPS

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations.
Use of FD or AP providing RNAV track guidance required during simultaneous operations.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C.
For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000 and LNAV Cat C/D visibility to 1½ NM.

ALSF-2

MISSED APPROACH: Climb to 1000 then climbing right turn to 2200 direct DUHAM and hold.

D-ATIS 123.8	RALEIGH APP CON 127.675 307.9	RALEIGH TOWER 127.45 257.8	GND CON 121.9 348.6	CINC DEL 120.1	CPDLC
------------------------	---	--------------------------------------	-------------------------------	--------------------------	-------



1000 ↑	2200 ↗	DUHAM △	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).			
RW23R 1.6 NM to RW23R BODY 2200 PRSTN DABKE MARBY 5000 234° 4000 3000 2200 GP 3.00° TCH 55 1.6 NM 3.9 NM 3 NM 2.7 NM 3.1 NM						
CATEGORY	A		B		C	D
LPV DA			609/18		200 (200-½)	
LNAV/VNAV DA			826/40		417 (400-¾)	
LNAV MDA	980/24		571 (600-½)		980-1¼ 571 (600-1¼)	
CIRCLING	980-1		545 (600-1)		1020-1½ 585 (600-1½) 1180-2½ 745 (800-2½)	