

WAAS CH 40212 W36A	APP CRS 005°	Rwy Ldg 11601 TDZE 92 Apt Elev 96
--	------------------------	--

RNAV (GPS) RWY 36R

ORLANDO INTL (MCO)


▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C (31°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000.

ALSF-2

MISSED APPROACH: Climb to 500 then dimbing left turn to 3000 direct DNMOR and hold, continue climb-in-hold to 3000.

D-ATIS ARR 121.25 DEP 120.525	ORLANDO APP CON 124.8 307.0	ORLANDO TOWER 118.45 253.5 (17L-35R, 17R-35L) 124.3 253.5 (18L-36R, 18R-36L)	GND CON 126.4 (E) 121.8 (W)	CLNC DEL 134.7 341.7	CPDLC
---	---------------------------------------	--	---	--	-------



500

3000

DNMOR

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).

*LNAV only.

1.2

3.4 NM

4.4 NM

3.2 NM

1.2

3.4 NM

4.4 NM

3.2 NM

1.2

3.4 NM

4.4 NM

3.2 NM

CATEGORY	A	B	C	D
LPV DA		292/18	200 (200-½)	
LNAV/VNAV DA		454/40	362 (400-¾)	
LNAV MDA	540/24	448 (500-½)	540/45	448 (500-¾)
CIRCLING	740-1	644 (700-1)	740-1¾ 644 (700-¾)	740-2 644 (700-2)

881

181

12004 X 200

12005 X 200

36L

36R

17L

17R

10000 X 150

9001 X 150

35L

35R

TWR

005°

HIRL all Rws

REIL Rwy 36L

TDZ/CL Rws 17L/R,

18R, 35L/R and 36R