



WAAS CH 40214 W22A	APP CRS 224°	Rwy Idg 10701 TDZE 1077 Apt Elev 1077
--	------------------------	--

RNAV (GPS) RWY 22R

WILMINGTON AIR PARK (ILN)

RNP APCH - GPS. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500.			ALSF-2 	MISSED APPROACH: Climb to 1500 then right turn 3000 direct TIGRR and hold.	
D-ATIS 124.925	COLUMBUS APP CON 118.85 269.275	WILMINGTON TOWER 119.475	GND CON 121.6	CLNC DEL 128.85	



1500	3000	TIGRR	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).	
		MURGE	2400	WIZRD
		1.2 NM to RWY 22R	2400	GP 3.00° TCH 55
		1.2 NM	2.8 NM	6 NM
CATEGORY	A	B	C	D
LPV DA	1277/18		200 (200-½)	
LNAV/VNAV DA	1393/24		316 (400-½)	
LNAV MDA	1520/24 443 (500-½)		1520/45 443 (500-¾)	
CIRCLING	1560-1 483 (500-1)		1860-2¼ 783 (800-2¼) 1860-2½ 783 (800-2½)	