

WAAS
CH **86919**
W17A

APP CRS
174°

Rwy Ldg
TDZE
Apt Elev
5997
1073
1073

RNAV (GPS) RWY 17

SHAWNEE RGNL (SNL)

▼ Baro-VNAV NA when using Seminole altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F).
▲ DME/DME RNP-0.3 NA. When local altimeter setting not received, use Seminole altimeter setting: increase LPV DA to 1313 feet; increase LNAV/VNAV DA to 1487 feet and visibility ¼ SM; increase all MDAs 40 feet and visibility Cat C ¼ SM.

MALSR

MISSED APPROACH: Climb to 4000 direct HEDEK and on track 179° to MINGG and hold.

AWOS-3PT
118.275

OKE CITY APP CON
120.45 288.325

UNICOM
122.7 (CTAF)

4000

HEDEK

↑

MINGG

↑

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 52).

4 NM Holding Pattern

*LNAV only.

OWNOJ 1.7 NM to RW17

GP 3.00° TCH 58

2800

174°

3000

354°

174°

1660

1.7

3.5 NM

6 NM

CATEGORY	A	B	C	D
LPV DA	1273-½	200 (200-½)		NA
LNAV/VNAV DA	1447-¾	374 (400-¾)		NA
LNAV MDA	1540-½	467 (500-½)	1540-¾ 467 (500-¾)	NA
CIRCLING	1600-1	527 (600-1)	1640-1½ 567 (600-1½)	NA

ELEV 1073

TDZE 1073

174°

↓

41

AS

100

5997 X 100

35

MIRL Rwy 17-35

REIL Rwy 17 and 35

SHAWNEE, OKLAHOMA
Amdt 1A 27FEB20

35°21'N-96°57'W

SHAWNEE RGNL (SNL)
RNAV (GPS) RWY 17

SC-1, 04 SEP 2025 to 02 OCT 2025

SC-1, 04 SEP 2025 to 02 OCT 2025