

|                                        |                        |                                                               |
|----------------------------------------|------------------------|---------------------------------------------------------------|
| WAAS<br>CH <b>87116</b><br><b>W20A</b> | APP CRS<br><b>205°</b> | Rwy Idg <b>5600</b><br>TDZE <b>568</b><br>Apt Elev <b>571</b> |
|----------------------------------------|------------------------|---------------------------------------------------------------|

RNAV (GPS) RWY 20  
DANVILLE RGNL (DAN)

RNP APCH.

**V** Baro-VNAV NA when using Roxboro, NC altimeter setting. For uncompensated  
**A** Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. When  
local altimeter setting not received, use Roxboro, NC altimeter setting and increase  
all DA 62 feet and all MDA 80 feet; increase LPV and LNAV/VNAV all Cats visibility  
¼ mile and LNAV Cats C and D ¼ mile. VDP NA with Roxboro, NC altimeter setting.

**MISSED APPROACH:** Climb to 2500 direct LANTA and hold.

|                        |                                          |                                  |
|------------------------|------------------------------------------|----------------------------------|
| ASOS<br><b>128.125</b> | WASHINGTON CENTER<br><b>124.05 352.0</b> | UNICOM<br><b>123.05 (CTAF) 0</b> |
|------------------------|------------------------------------------|----------------------------------|

