

WAAS CH 93808 W35A	APP CRS 355°	Rwy Idg TDZE Apt Elev	7201 1008 1009
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35

PONCA CITY RGNL (PNC)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 46°C (114°F). DME/DME RNP-0.3 NA. When local altimeter setting not received use Winfield-Arkansas City altimeter setting and increase LPV DA to 1377 feet, LNAV/VNAV DA to 1560 feet and all MDA 100 feet; increase LPV all Cats, LNAV/VNAV all Cats, LNAV Cats C and D and Circling Cats C and D visibility ¼ SM. Baro-VNAV NA when using Winfield-Arkansas City altimeter setting. Visibility reduction by helicopters NA.

ODALS

MISSED APPROACH:

Climb to 2800 direct TOMHO and hold.

ASOS 134.075	KANSAS CITY CENTER 127.8 319.1	UNICOM 123.0 (CTAF) 0
------------------------	--	---------------------------------

MISSED APCH FIX

ELEV 1009

TDZE 1008

HIRL Rwy 17-35 0

4 NM Holding Pattern

GP 3.00° TCH 45

CATEGORY	A	B	C	D
LPV DA	1295-1 287 (300-1)			
LNAV/VNAV DA	1478-1¾ 470 (500-1¾)			
LNAV MDA	1540-1 532 (600-1)	1540-1½ 532 (600-1½)	1540-1¾ 532 (600-1¾)	1540-1¾ 532 (600-1¾)
CIRCLING	1540-1 531 (600-1)	1580-1 571 (600-1)	1800-2¼ 791 (800-2¼)	1880-2¾ 871 (900-2¾)

PONCA CITY, OKLAHOMA
Amdt 1A 09SEP21

36°44'N-97°06'W

PONCA CITY RGNL (PNC)

RNAV (GPS) RWY 35