WAAS CH 90132 W06A	APP CRS 060°	Rwy ldg 5188 TDZE 586 Apt Elev 592

RNAV (GPS) RWY 6
NIAGARA FALLS INTL (IAG)

RNP APCH.

Baro-VNAV NA when using Buffalo Niagara Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). When local altimeter setting not received, use Buffalo Niagara Intl altimeter setting and increase all DA 51 feet and all MDA 60 feet, increase LNAV Cat C and D visibility ⅛ SM and Circling Cat C and D ¼ SM. Rwy 6, 10R, 24, 28L helicopter visibility reduction below 1 SM NA. Straight-in Rwy 6 NA at night, Circling Rwy 6, 10R, 24, 28L NA at night.

MISSED APPROACH: Climb to 3600 direct ZUPUV and hold.

ATIS	BUFFALO APP CON	NIAGARA TOWER*	GND CON	CLNC DEL	UNICOM
120.8 269.4	126.5 317.6	118.5 (CTAF) L 349.0	125.3 275.8	119.25 251.1	122.95



RADAR REQUIRED



CATEGORY	A	B	C	D
LPV DA	864-1		278 (300-1)	
LNAV/VNAV DA	849-1		263 (300-1)	
LNAV MDA	940-1		354 (400-1)	
C CIRCLING	1100-1 508 (600-1)		1280-2 688 (700-2)	1280-2¼ 688 (700-2¼)

NE-2, 04 SEP 2025 to 02 OCT 2025