

WAAS CH 99732 W10A	APP CRS 101°	Rwy Idg 8005 TDZE 38 Apt Elev 40
--	------------------------	---

RNAV (GPS) RWY 10

Wallops Flight Facility (WAL)

▼

DME/DME RNP -0.3 NA. Rwy 10 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Salisbury altimeter setting and increase all DA 60 feet and all visibilities ¼ SM. Increase all MDA 60 feet and all Cat C and D visibilities ¼ SM. Baro-VNAV and VDP NA when using Salisbury altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 54°C (130°F).

▲

MISSED APPROACH: Climb to 700 then climbing left turn to 2000 direct MAGGO and hold.

ASOS 119.175	PATUXENT APP CON ★ 127.95 314.0	Wallops Tower ★ 126.5 (CTAF) 306.975 (CTAF)	GND CON 127.875 269.325	CLNC DEL 121.7
------------------------	---	---	-----------------------------------	--------------------------

The main chart displays the RNAV (GPS) RWY 10 approach. Key features include:

- Approach Path:** Starts at 101° heading, passing through the (IF/IAF) WERIV fix. The path continues to the XECPI 2.5 NM to RW10, then to the RW10 fix, and finally to the runway threshold at 101°.
- Holding Patterns:** A 5 NM holding pattern is shown at WERIV, and another 5 NM holding pattern is shown at MAGGO.
- Obstacles:** Various obstacles are marked, including R-4006, R-6604D, R-6604A, R-6604E, and R-6604B.
- Navigation Aids:** The chart includes the WERIV VORTAC and the MAGGO VORTAC.
- Altitudes:** The chart shows various altitudes, including 101°, 1700, 2000, 241, 253, 315, 350, 400, 450, 508, 749, and 800.
- Distance Markers:** Distances are marked along the approach path, including 5 NM, 2.5 NM, 1.5 NM, and 1 NM.
- Other Information:** The chart includes the text "DME/DME RNP -0.3 NA" and "RNAV (GPS) RWY 10".

5 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69°).		700 2000 MAGGO	
2000 ← 281° 101° →		BIKTE 1700		*LNAV only.	
GP 3.00° TCH 60		XECPI 2.5 NM to RW10		*1 NM to RW10	
6 NM		2.6 NM		1.5 NM	
1 NM		860		RW10	
CATEGORY	A	B	C	D	
LPV DA	330-1	292 (300-1)			
LNAV/VNAV DA	443-1¼	405 (500-1¼)			
LNAV MDA	420-1 382 (400-1)	420-1½ 382 (400-1½)			
CIRCLING	600-1 560 (600-1)	620-1½ 580 (600-1½)	860-2¾ 820 (900-2¾)		

Wallops Island, Virginia

Amtd 2 05JAN17

37°56'N-75°28'W

Wallops Flight Facility (WAL)

RNAV (GPS) RWY 10