

LOC I-PKB <u>110.7</u>	APP CRS 027°	Rwy Idg TDZE Apt Elev	6780 830 859
----------------------------------	------------------------	-----------------------------	---


ILS or LOC RWY 3
MID-OHIO VALLEY RGNL (PKB)

T Circling Rwy 10, 28 NA at night. Rwy 3 helicopter visibility reduction below RVR 4000 NA. When local altimeter setting not received, use Athens/Albany altimeter setting: increase DA to 1301 feet and visibility all Cats ¼ SM; increase all MDAs 100 feet and visibility Cats C and D ½ SM. For inop ALS, increase S-LORC 3 Cat A/B and S-LOC 3 HADUP fix minimums (DME required) Cat A/B visibility to RVR 5500. For inop ALS when using Athens/Albany altimeter setting, increase S-LS 3 all Cats visibility to 1½ SM and S-LOC 3 all Cats and S-LOC 3 HADUP fix minimums (DME required) Cat A/B visibility to RVR 5500.

MALSR

MISSED APPROACH:
Climb to 1400 then
climbing right turn to
2700 direct JPU
VOR/DME and hold.

ATIS 124.35	INDIANAPOLIS CENTER 125.55 317.475	PARKERSBURG TOWER ★ 123.7 (CTAF) 0 257.8	GND CON 126.45	UNICOM 122.95
----------------	---------------------------------------	---	-------------------	------------------



One Minute Holding Pattern

VERS LOM
JPU [12.3]

2592

1400

2700

JPU

10000

2600

← 207°

027° →

2600

GS 3.00°
TCH 49

HADUP
JPU [8.8]

JPU [7]

* LOC only 1480 when using Athens/Albany climb setting.

*1380

3.5 NM

1.8

CATEGORY	A	B	C	D
S-ILS 3		1201/40 371 (400-¾)		
S-LOC 3	1380/40	550 (600-¾)	1380/60	550 (600-1¼)
CIRCLING	1380-1	521 (600-1)	1640-2½ 781 (800-2¼)	1640-2½ 781 (800-2½)

HADUP FIX MINIMUMS (DME REQUIRED)

S-LOC 3	1260/40 430 (500-¾)		
CIRCLING	1320-1 461 (500-1)	1380-1 521 (600-1)	1640-2½ 781 (800-2¼)

[illegible]