


WAAS CH 58207 W25A	APP CRS 252°	Rwy Idg 4872 TDZE 659 Apt Elev 684
--	------------------------	---

RNAV (GPS) RWY 25
IOWA CITY MUNI (IOW)

RNP APCH - GPS.	
V Rwy 25 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C. Circling Rwy 12, 30 NA at night. Baro-VNAV and VDP NA when using CID altimeter setting. When local altimeter setting not received, use CID altimeter setting: increase LPV DA to 970 feet and all visibilities $\frac{1}{8}$ SM; increase LNAV/VNAV DA to 1209 feet and all visibilities $\frac{1}{4}$ SM; increase all MDAs 80 feet and LNAV visibility Cats C/D $\frac{3}{8}$ SM, and Circling visibility Cat C/D $\frac{1}{4}$ SM.	MISSED APPROACH: Climb to 1200 then climbing left turn to 2600 direct IOW VOR/DME and hold, continue climb-in-hold to 2600.

ASOS 128.075	CEDAR RAPIDS APP CON ★ 119.7 266.8	CLNC DEL 119.05	UNICOM 122.8 (CTAF) 0
------------------------	--	---------------------------	--



NC-3, 04 SEP 2025 to 02 OCT 2025

ELEV 684	D	TDZE 659
----------	----------	----------

