


VOR/DME RIW 114.05 Chan 87(Y)	APP CRS 101°	Rwy Idg 8204 TDZE 5516 Apt Elev 5516
---	------------------------	---

VOR RWY 10
CENTRAL WYOMING RGNL (RIW)

⚠ When local altimeter setting not received, use Lander altimeter setting and increase all MDA 60 feet and increase S-10 Cat C and D visibility ¼ mile and Circling Cat C visibility ½ mile, increase WUNIB fix minimums Cat C and D visibility ½ mile. Rwy 10 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 7900 in RIW VOR/DME holding pattern.

ASOS 121.425	SALT LAKE CENTER 133.25 285.6	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



ELEV 5516 **D** TDZE 5516

7900 RIW

101° to VOR/DME

1.1% DOWN 61
8204 X 1.50
0.4% UP 4800 Y 171
0.7% UP 5513
AS 28

Remain within 10 NM

PYLOT INT RIW 6.5

7800

101°

*6060 when using Lander altimeter setting.

7400

3.00° TCH 50

WUNIB RIW 2.2

RIW VOR/DME

*6000

4.3 NM 1.4 NM

CATEGORY	A	B	C	D
S-10	6000-1	484 (500-1)	6000-1 ¾	484 (500-1 ¾)
C CIRCLING	6000-1	484 (500-1)	6000-1 ½	6120-2 484 (500-1 ½) 604 (600-2)
WUNIB FIX MINIMUMS (DME REQUIRED)				
S-10	5940-1	424 (500-1)	5940-1 ¼	424 (500-1 ¼)
C CIRCLING	6000-1	484 (500-1)	6000-1 ½	6120-2 484 (500-1 ½) 604 (700-2)

NW-1, 04 SEP 2025 to 02 OCT 2025

NW-1, 04 SEP 2025 to 02 OCT 2025