

25107

RNAV (GPS) Y RWY 30L
NORMAN Y MINETA SAN JOSE INTL (SJC)

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 1°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 1½ SM.
* RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR
Rwy 30L

MISSED APPROACH: Climb to 2300 direct MUSSK and hold.

Procedure NA for arrivals at BORED on V301 southeast bound and on T333 northbound.

(IAF) BORED

(IAF) SWIGS

(IAF) KLIDE 230K

(FAF) ZULUP

(FAF) HIVAK

FORUL 2.8 NM to RW30L

MSA RW30L 2.5 NM

5600

4 NM

MUSK

251

183

284

376

396

265

426

542

713

260

1435

306

400

230K

3660

5200

221

110.4

3216

3104

3460

4400

2502

2457

1863

1833

3951

3841

3817

4089

3672

3720

3049

2912

3231

2628

2334

1365

857

1206

2945

4084

2800

ELEV 62

D

TDZE 30L 57

TDZE 30R 55

REIL Rwy 12L
HIRL Rwy 12L-30R and 12R-30L

NORMAN Y MINETA SAN JOSE INTL (SJC)
RNAV (GPS) Y RWY 30L

SW-2, 04 SEP 2025 to 02 OCT 2025