

VOR/DME OWB

108.65

Chan 23(Y)

APP CRS

005°

Rwy Idg

8000

TDZE

401

Apt Elev

407

OWENSBORO/DAVIESS COUNTY RGNL (OWB)

VOR RWY 36

For inop ALS, increase S-36 Cat C and D visibility to 2 SM and BIYAC fix minimums S-36 Cat C and D visibility to 1½ SM.

MALSR

MISSED APPROACH: Climb to 2500 then left turn direct OWB VOR/DME and hold.

AWOS-3PT	EVANSVILLE APP CON ★	OWENSBORO TOWER ★	GND CON	UNICOM
119.025	124.025 290.9	120.7 (CTAF) 251.15	121.7	122.95

Procedure NA for arrival on PXV
VORTAC airway radials 081 CW 141.

ELEV 407	TDZE 401
----------	----------

Remain within 10 NM

OWB VOR/DME

6000

2100

185°

005°

1140

3.06°

TCH 56

1 NM

1.2 NM

2500

OWB

81

486

466

5000 X 1000

36

005°

MIRL Rwy 6-24

HIRL Rwy 18-36

REIL Rwy 6, 18 and 24

CATEGORY	A	B	C	D
S-36	1140-½	739 (800-½)	1140-1⅝	739 (800-1⅝)
CIRCLING	1140-1	733 (800-1)	1140-2	1140-2¼
			733 (800-2)	733 (800-2¼)
BIYAC FIX MINIMUMS				
S-36	820-½	419 (500-½)	820-¾	419 (500-¾)
CIRCLING	860-1	1120-1	1140-2	1140-2¼
	453 (500-1)	713 (800-1)	733 (800-2)	733 (800-2¼)

OWENSBORO, KENTUCKY

OWENSBORO/DAVIESS COUNTY RGNL (OWB)

Amdt 19C 26MAR20

37°44'N-87°10'W

VOR RWY 36