

TACAN RWY 07

TACAN LRF
Chan 29

APCH CRS
058°

Rwy ldg 12,001
TDZE 310
Arpt Elev 312

[USAF]

LITTLE ROCK AFB (KLRF)

▼ * When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1 7/8 miles.
** Circling not authorized S of Rwy 07-25.

ALSF-1
A1

MISSED APPROACH: Climbing left turn turn to 3000 to intercept LRF R-342 outbound to HERCK and hold as published.

ATIS★
119.175 251.1

APP CON/DEP CON
119.5 306.2

TOWER
120.6 269.075

GND CON
132.8 275.8

CLNC DEL★
253.5

LRF 17

HOLD 4000 3000

ATC RADAR required for holding above 4000' or greater than 200 KIAS.

HERCK LRF 13

R-342

JACKSONVILLE Chan 29 LRF

R2403A

R2403B

Approach not authorized when R2403B is active.

ATC RADAR required for holding above 6000' or greater than 230 KIAS.

HOLD 6000 3200

1096 LRF 17

238° 230K 058°

(IF/IAF) HURKO LRF 13

1800 058° (7.6)

ROCK LRF 5.4

CUTUM LRF 1

EMERG SAFE ALT 100NM 4000

LRF 17

HURKO LRF 13

ROCK LRF 5.4

CUTUM LRF 1

HERCK LRF 13

3000 LRF R-342

TACAN

3200 058°

238°

058°

058°

1800

2.83° TCH 50

4.4 NM

0.5

ELEV 312

TDZE 310

ASSAULT STRIP 072° 252° 3361 x 60 12,001 x 150

TWR

058°

CATEGORY	A	B	C	D	E
S-07 *	980/40 670 (700-3/4)		980-1 1/2 670 (700-1 1/2)		
CIRCLING **	980-1 668 (700-1)		980-1 7/8 668 (700-1 7/8)	1040-2 1/4 728 (800-2 1/4)	1040-2 1/2 728 (800-2 1/2)

HIRL Rwy 07-25
TDZL/CL Rwy 25

ALTERNATE MISSED APPROACH: Climbing to 3000 fly runway heading until LRF 2 DME, then turn left heading 360°, EFC from ATC.

SC-1, 04 SEP 2025 to 02 OCT 2025

SC-1, 04 SEP 2025 to 02 OCT 2025

JACKSONVILLE, ARKANSAS
Orig 11JUL24

34° 55'N - 92° 09'W

LITTLE ROCK AFB (KLRF)

TACAN RWY 07