

LOC I-JBD	APP CRS	Rwy Idg	5343
108.95	053°	TDZE	124
		Apt Elev	125

ILS or LOC RWY 5
LUMBERTON RGNL (LBT)

ADF required.


▼

▲

When local altimeter setting not received, use Maxton altimeter setting and increase DA to 416 feet and all visibility $\frac{1}{8}$ SM; increase all MDA to 60 feet and S-LOC 5 visibility Cat C $\frac{1}{8}$ SM and Circling visibility Cat C $\frac{1}{4}$ SM. Circling Rwy 13, 31 NA at night. Autopilot coupled approach NA below 1250.

MISSED APPROACH: Climb to 1000 then climbing right turn to 1900 direct JIGEL LOM and hold.

ASOS 134.775	FAYETTEVILLE APP CON 133.0 290.25	UNICOM 122.8 (CTAF) 0
-----------------	--------------------------------------	--------------------------



One Minute Holding Pattern			
JB JIGEL LOM			
1799			
1900			
GS 3.00° TCH 60			
233°			
053°			
1900			
4.6 NM			
0.4			
CATEGORY	A	B	C
S-ILS 5	360- $\frac{3}{4}$	236 (300- $\frac{3}{4}$)	NA
S-LOC 5	600-1	476 (500-1)	600-1 $\frac{3}{8}$ 476 (500-1 $\frac{3}{8}$)
CIRCLING	660-1	535 (600-1)	720-1 $\frac{1}{2}$ 595 (600-1 $\frac{1}{2}$)

