

WAAS CH 69208 W33B	APP CRS 335°	Rwy Ldg TDZE 124 Apt Elev 143
--	------------------------	---

BALTIMORE/

RNAV (GPS) RWY 33R

WASHINGTON INTL THURGOOD MARSHALL (BWI)

RNP APCH - GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. For inop MALS, increase LNAV/VNAV all Cats visibility to RVR 5000 and LNAV all Cats visibility to RVR 5500. Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. Helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to LPV, all Cats.

MALS

MISSED APPROACH:
Climb to 3000 direct
KRENE and hold.

D-ATIS 115.1 127.8	POTOMAC APP CON 119.0 282.275 124.55 317.425 (020°-100°) 119.7 290.475 (131°-180°) (101°-130°) 128.7 307.9 (181°-019°)	BALTIMORE TOWER 119.4 257.8	GND CON 121.9	CLNC DEL 118.05
------------------------------	--	---------------------------------------	-------------------------	---------------------------

CPDLC

ELEV 143 **D** TDZE 124

TDZ/CL Rws 10 and 33L
REIL Rws 15L and 33R
HIRL all Rws

3000	KRENE	DUDDS		
3000	EXEVE 2.5 NM to RW33R	ORiol 2000		
1.1 NM to RW33R	1.4 NM	3.3 NM	6.3 NM	
940	2000	GP 3.00° TCH 47		
335°				
CATEGORY	A	B	C	D
LPV DA	333/40	209 (200-¾)	NA	NA
LNAV/VNAV DA	406/40	282 (300-¾)	NA	NA
LNAV MDA	520/40	396 (400-¾)	NA	NA
CIRCLING	640-1 497 (500-1)	660-1 517 (600-1)	NA	NA

BALTIMORE, MARYLAND
Amdt 4B 11AUG22

BALTIMORE/WASHINGTON INTL THURGOOD MARSHALL (BWI)
39°11'N-76°40'W

RNAV (GPS) RWY 33R