

WAAS
CH **45616**
W23A

APP CRS
233°

Rwy Idg
TDZE
Apt Elev
6215
931
947

RNAV (GPS) Y RWY 23
WEST VIRGINIA INTL YEAGER (CRW)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inoperative ALSF, increase LNAV/VNAV all Cats visibility to 2¼. **RVR 1800 authorized with use of FD or AP or HUD to DA.

ALSF-1

ⓐ1

ⓐ1

MISSED APPROACH: Climb to 1400 then dimbing right turn to 3000 direct HVQ VOR/DME and hold.

ATIS 127.6	CHARLESTON APP CON 124.1 269.125	CHARLESTON TOWER 125.7 257.8	GND CON 121.8 348.6	CLNC DEL 118.55
----------------------	--	--	-------------------------------	---------------------------

ELEV 947

D

TDZE 931

1400

3000

HVQ

⬆

⤴

◻

*LNAV only.

COSIK

ENIVY

ZUPUT

2.3 NM to RW23

1400

2400

1400

3000

053°

233°

3000

1.7 NM

0.6 NM

2.2 NM

6.5 NM

GP 3.00°

TCH 56

CATEGORY	A	B	C	D
LPV	DA**	1131/24	200 (200-½)	
LNAV/VNAV	DA	1601-1⅞	670 (700-1⅞)	
LNAV	MDA	1500/24 569 (600-½)	1500-1⅓ 569 (600-1⅓)	
CIRCLING		1600-1 653 (700-1)	1760-2½ 813 (900-2½)	1760-2¾ 813 (900-2¾)

CHARLESTON, WEST VIRGINIA
Amdt 1B 07DEC17

38°23'N-81°36'W

WEST VIRGINIA INTL YEAGER (CRW)
RNAV (GPS) Y RWY 23