

APP CRS	Rwy Ldg	9007
020°	TDZE	2966
	Apt Elev	2977

RNAV (RNP) Y RWY 2
GLACIER PARK INTL (GPI)

RF and GPS required. Missed approach requires RNP less than 1.0.
For uncompensated Baro-VNAV systems, procedure NA below -21°C (-5°F) or above 43°C (109°F). For inoperative MALSR increase RNP 0.10* visibility to 1¼ and RNP 0.30 visibility to 2.
*Missed approach requires minimum climb of 220 feet per NM to 6100.

MALSR
A5

MISSED APPROACH: Climb to 10000 via left turn to JOGAD, and via left turn to TONUUY, and via 121° track to WILTO and via 129° track to ANGLI and hold.

ATIS 132.625	SALT LAKE CENTER 127.075 244.875	GLACIER TOWER ★ 124.55 (CTAF) 0	GND CON 121.6	UNICOM 122.95
-----------------	-------------------------------------	------------------------------------	------------------	------------------



ELEV 2977 **D** TDZE 2966

TWR ★

REIL Rwy 20 0

MIRL Rwy 12-30 0

HIRL Rwy 2-20 0

Procedure Turn NA		10000 JOGAD		ROYOG	
JUNRU		WULEX		AVDIH	
8000 015°		7200 020°		5200	
GP 3.00°		5200		RWY 2	
TCH 51		3 NM		6.7 NM	
CATEGORY		A		D	
RNP 0.10 DA*		NA		3340-¾ 374 (400-¾)	
RNP 0.30 DA		NA		3522-1½ 556 (600-1½)	