

LOC/DME I-REE	APP CRS	Rwy Idg	7302
111.35	316°	TDZE	806
Chan 50 (Y)		Apt Elev	808

ILS or LOC RWY 32

SOUTHERN WISCONSIN RGNL (JVL)

DME required. RNP APCH - GPS.


⚠

Circling Rwy 18 NA at night. When local altimeter setting not received, use Chicago/Rockford Intl altimeter setting and increase DA to 1075, increase all MDA 80 feet. Increase S-LOC 32 Cats C and D visibility ¾ SM, and Circling Cats C/D ¼ SM. VDP NA when using Chicago/Rockford Intl altimeter setting. For inop ALS when using Chicago/Rockford Intl altimeter setting, increase S-ILS 32 visibility all Cats to ¾ SM and S-LOC 32 visibility Cats C/D to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 1700 then climbing left turn to 3100 direct TIRRO and hold.

ATIS	ROCKFORD APP CON	JANESVILLE TOWER ★	GND CON	CLNC DEL	UNICOM
128.25	121.0 327.0	118.8(CTAF) 225.4	121.65	121.65	122.95



	ELEV 808	TDZE 806
	HIRL Rwy 4-22 and 14-32	
	MIRL Rwy 18-36	
	REIL Rwy 14 and 22	
	4 NM Holding Pattern	
	GS 3.00° TCH 52	
CATEGORY	A	B
S-ILS 32	1006-½	200 (200-½)
S-LOC 32	1200-½ 394 (400-½)	1200-¾ 394 (400-¾)
CIRCLING	1260-1 452 (500-1)	1320-1 512 (600-1)

FAF to MAP 5.4 NM				
Knots	60	90	120	150
Min:Seq	5:24	3:36	2:42	2:10

EC-3, 04 SEP 2025 to 02 OCT 2025

EC-3, 04 SEP 2025 to 02 OCT 2025