

LOC I-JVL	APP CRS	Rwy Idg	6701
109.1	044°	TDZE	806
		Apt Elev	808

ILS or LOC RWY 4

SOUTHERN WISCONSIN RGNL (JVL)



DME required. RNP APCH - GPS.

When local altimeter setting not received, use Rockford altimeter setting and increase DA 69 feet and all MDAs 80 feet; increase S-LOC 4 Cats C/D and Circling Cats C/D ¼ SM. For inop ALS when using Rockford altimeter setting; increase S-ILS 4 all Cats visibility to ¾ SM and S-LOC 4 Cats C/D visibility to 1½ SM. Circling Rwy 18 NA at night. DME from JVL VOR/DME. DME use requires simultaneous reception of I-JVL and JVL VOR/DME.

MALSR

MISSED APPROACH:
Climb to 3100 direct
OTLEE and hold.

ATIS	ROCKFORD APP CON	JANESVILLE TOWER ★	GND CON	CLNC DEL	UNICOM
128.25	121.0 327.0	118.8(CTAF) 225.4	121.65	121.65	122.95



ELEV 808	TDZE 806
REIL Rwy 14 and 22	
MIRL Rwy 18-36	
HIRL Rwy 4-22 and 14-32	
FAF to MAP 5.7 NM	
Knots	60 90 120 150 180
Min:Sec	5:42 3:48 2:51 2:17 1:54