

LOC/DME I-MVP 111.55 Chan 52 (Y)	APP CRS 196°	Rwy Ldg 7302 TDZE 1320 Apt Elev 1333
--	------------------------	---

ILS or LOC RWY 19L
WICHITA DWIGHT D EISENHOWER NTL (ICT)



⚠ ADF required. Simultaneous approach authorized with ILS or LOC RWY 19R. For inoperative MALS, increase S-ILS 19L Cat E visibility to ¾ mile, S-LOC 19L Cat E visibility to 1 ½ mile, NUMAE fix minimums: S-LOC 19L Cat C/D/E visibility to 1 mile.

MALS



MISSED APPROACH: Climb to 3000 direct PICHE LOM and hold.

ATIS 125.15	WICHITA APP CON 126.7 353.5	WICHITA TOWER 118.2 257.8	GND CON 121.9 348.6	CLNC DEL 125.7
-----------------------	---------------------------------------	-------------------------------------	-------------------------------	--------------------------



CATEGORY		A	B	C	D	E
S-ILS 19L		1520-½ 200 (200-½)				
S-LOC 19L		1780-½ 460 (500-½)		1780-⅞ 460 (500-⅞)		
CIRCLING		1800-1 467 (500-1)	1980-1¾ 647 (700-1¾)	1980-2 647 (700-2)	2000-2¼ 667 (700-2¼)	2000-2¼ 667 (700-2¼)
NUMAE FIX MINIMUMS (DME REQUIRED)						
S-LOC 19L		1700-½ 380 (400-½)		1700-⅝ 380 (400-⅝)		
CIRCLING		1800-1 467 (500-1)	1980-1¾ 647 (700-1¾)	1980-2 647 (700-2)	2000-2¼ 667 (700-2¼)	2000-2¼ 667 (700-2¼)

NC-2, 04 SEP 2025 to 02 OCT 2025

NC-2, 04 SEP 2025 to 02 OCT 2025