



LOC I-HUM <u>108.5</u>	APP CRS 179°	Rwy Ldg 6143 TDZE 8 Apt Elev 9
----------------------------------	------------------------	---

ILS or LOC RWY 18

T When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting: increase DA to 285 feet; increase all MDA 80 feet and S-LOC 18 Cat C/D visibility $\frac{1}{4}$ SM and Circling Cat C/D visibility $\frac{1}{4}$ SM. For inop ALS increase S-LOC 18 Cat C/D visibility to 1 SM. For inop ALS when using Louis Armstrong New Orleans Intl altimeter setting increase S-ILS 18 all Cats visibility $\frac{1}{8}$ SM.	MALSR 	MISSED APPROACH: Climb to 1100 then climbing left turn to 1800 on heading 050° and BOLD VOR/DME R-122 to BOURG INT/TBD 16.3 DME and hold.
--	---	---

ATIS 120.25	NEW ORLEANS APP CON 118.9 350.35	HOUMA TOWER ★ 125.3 (CTAF) 0 346.3	GND CON 123.875	CLNC DEL 118.9 (When twr closed)	UNICOM 122.95
-----------------------	--	--	---------------------------	---	-------------------------



CATEGORY	A	B	C	D
S-ILS 18	208- $\frac{1}{2}$ 200 (200- $\frac{1}{2}$)			
S-LOC 18	380- $\frac{1}{2}$ 372 (400- $\frac{1}{2}$)		380- $\frac{5}{8}$ 372 (400- $\frac{5}{8}$)	
C CIRCLING	480-1 471 (500-1)		760-2 $\frac{1}{4}$ 751 (800-2 $\frac{1}{4}$)	760-2 $\frac{1}{2}$ 751 (800-2 $\frac{1}{2}$)

