

LOC/DME I-LHJ

111.55

APP CRS

201°

Rwy Ldg

8000

TDZE

871

Chan

52(Y)

Apt Elev

871

ILS or LOC RWY 20

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

ADF or DME or RADAR required for LOC only.
RADAR required for procedure entry at OLIDE.

VDP NA when using PIA altimeter setting. When local altimeter setting not received, use PIA altimeter setting: increase S-ILS 20 DA to 1187 feet and all visibilities to RVR 2400; increase all MDAs 120 feet and S-LOC 20 visibility Cats C and D to RVR 5500 and Circling visibility Cats C and D ¼ SM. For inop ALS when using PIA altimeter setting, increase S-ILS 20 all Cats visibility to RVR 4500 and S-LOC 20 Cats C and D visibility to 1¾ SM.

ALSF-2

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 on heading 279° and SPI VORTAC R-037 to MCLEN INT/PIA 34.2 DME and hold, continue climb-in-hold to 3000.

ATIS

119.575

SAINT LOUIS APP CON

128.725 256.9

BLOOMINGTON TOWER

124.6 (CTAF) 269.575

GND CON

121.65

UNICOM

122.95

ALTERNATE MISSED APCH FIX

LOM EGROW
I-LHJ 4.6
LH : : : :
334

1500

3000

hdg 279°

SPI

R-037

MCLEN

△

LH LOM EGROW

I-LHJ 4.6

Remain within 10 NM

CATEGORY	A	B	C	D
S-ILS 20	1071/18		200 (200-½)	
S-LOC 20	1260/24 389 (400-½)		1260/35 389 (400-¾)	
CIRCLING	1340-1 469 (500-1)		1620-2¼ 749 (800-2¼) 1620-2½ 749 (800-2½)	

ELEV 871

TDZE 871

TDZ/CL Rwy 20

HIRL Rwy 2-20 and 11-29

FAF to MAP 4.8 NM

Knots	60	90	120	150	180
Min:Sec	4:48	3:12	2:24	1:55	1:36

BLOOMINGTON/NORMAL, ILLINOIS

Amdt 4A 20FEB25

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

40°29'N-88°55'W

ILS or LOC RWY 20