

WAAS CH 60909 W29A	APP CRS 291°	Rwy Ldg 6525 TDZE 871 Apt Elev 871
--	------------------------	---

RNAV (GPS) RWY 29

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using General Downring-Peoria Intl altimeter setting. When local altimeter setting not received, use General Downring-Peoria Intl altimeter setting: increase all DA 116 feet and all MDA 120 feet; increase LPV all Cats visibility to RVR 3500, LNAV/VNAV all Cats and LNAV Cats C/D visibility ¾ mile, and Circling Cats C/D visibility ¼ mile. For inoperative MALSrs when using General Downring-Peoria Intl Regional altimeter setting increase LPV all Cats visibility ½ mile, and LNAV Cat C/D visibility ¾ mile.

MALSR

MISSED APPROACH:
Climb to 2500 direct
ZEXED and hold.

ATIS	SAINT LOUIS APP CON
119.575	128.725 256.9

BLOOMINGTON TOWER ★
124.6 (CTAF) **L** 269.575

GND CON
121.65

UNICOM
122.95

Procedure NA for arrivals at JILLY
via V173 northeast bound and
V227 northwest bound.

PW/29

(FAF
TEDO

(IAF)
LIPIC

 JILLY

WAPIX

EWITT

Procedure NA for arrivals at
EWITT via V313 southbound
and V233 southwest bound.

ELEV 871	D	TDZE 871
----------	----------	----------

TDZE 871

2500	ZEXED
------	-------

4 NM
Holding Pattern

* LNAV on

*1.6 NM to
RW29

TEDDY

WAPIX

3100

$$\frac{111^\circ \rightarrow}{\text{---}} 3100$$

GP 3.00°
TCH 56

CATEGORY		A	B	C	D
LPV	DA	1121/24 250 (300-½)			
LNAV/ VNAV	DA	1304/50 433 (500-1)			
LNAV	MDA	1460/24 589 (600-½)	1460-1¼ 589 (600-1¼)		
CIRCLING		1460-1 589 (600-1)	1620-2¼ 749 (800-2¼)	1620-2½ 749 (800-2½)	

BLOOMINGTON/NORMAL, ILLINOIS

Amdt 1A 15OCT15

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

40°29'N-88°55'W

RNAV (GPS) RWY 29

EC-3, 04 SEP 2025 to 02 OCT 2025

EC-3, 04 SEP 2025 to 02 OCT 2025