

▼

NA

Inop table does not apply to S-ILS 6 all Cats and S-LOC 6 Cats A and B. For inop ALS, increase S-LOC 6 Cat C/D visibility to 1 3/8 SM. Circling NA for Cat D northwest of Rwy 6-24.

MALSR

MISSED APPROACH: Climb to 3000 then climbing right turn to 5000 direct PSK VORTAC and hold, continue climb-in-hold to 5000.

|                   |                                |                           |                          |
|-------------------|--------------------------------|---------------------------|--------------------------|
| AWOS-3<br>127.375 | ROANOKE APP CON<br>126.0 339.8 | ROANOKE CLNC DEL<br>121.7 | UNICOM<br>122.7 (CTAF) 0 |
|-------------------|--------------------------------|---------------------------|--------------------------|

|                                                                                                      |                       |                       |                       |                               |
|------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-----------------------|-------------------------------|
| ELEV 2105                                                                                            |                       | TDZE 2105             |                       |                               |
| <div>One Minute Holding Pattern</div> <div></div>                                                    |                       |                       |                       |                               |
| CATEGORY                                                                                             | A                     | B                     | C                     | D                             |
| S-ILS 6                                                                                              |                       | 2305-1                | 200 (200-1)           |                               |
| S-LOC 6                                                                                              |                       | 2560-1                | 455 (500-1)           |                               |
| CIRCLING                                                                                             | 2620-1<br>515 (600-1) | 2680-1<br>575 (600-1) | 2780-2<br>675 (700-2) | 2780-2 1/4<br>675 (700-2 1/4) |
| FAF to MAP 5.1 NM                                                                                    |                       |                       |                       |                               |
| HIRL Rwy 6-24 0<br>REIL Rwy 24 0                                                                     |                       |                       |                       |                               |
| <div>Knots</div> <div>60 90 120 150 180</div> <div>Min:Sec</div> <div>5:06 3:24 2:33 2:02 1:42</div> |                       |                       |                       |                               |

DUBLIN, VIRGINIA

37°08'N-80°41'W

NEW RIVER VALLEY (PSK)

ILS or LOC Z RWY 6

Amdt 5B 25FEB21