


VORTAC SBV	APP CRS	Rwy Ldg	N/A
110.4	081°	TDZE	N/A
Chan 41		Apt Elev	420

VOR-A

WILLIAM M TUCK (W78)

V A Night landing: Rwy 19 NA. Helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Danville altimeter setting and increase all MDA 80 feet; increase all Cats visibility and DICYE fix minimums Cat C visibility ¼ mile. Circling NA to Rwy 6-24.	MISSED APPROACH: Climbing left turn to 3000 direct SBV VORTAC and hold.
--	--

AWOS-3 119.425	WASHINGTON CENTER 124.05 352.0	UNICOM 122.8 (CTAF) 0
-------------------	-----------------------------------	---------------------------------



Remain within 10 NM

3000 261° SBV VORTAC

081° 3000

*1280 when using Danville altimeter setting.

DICYE SBV [6.8]

MACPO SBV [8.1]

*1200

6.8 NM 1.3 NM

CATEGORY	A	B	C	D
C CIRCLING	1200-1	780 (800-1)	1200-2¼ 780 (800-2¼)	NA
DICYE FIX MINIMUMS				
C CIRCLING	960-1	540 (600-1)	1060-1¾ 640 (700-1¾)	NA

ELEV 420

081°

0.7% Up

2065 X 200

0.9% Up

1

MIRL Rwy 1-19 **0**

REIL Rwys 1 and 19 **0**

FAF to MAP 8.1 NM

Knots	60	90	120	150	180
Min:Sec	8:06	5:24	4:03	3:14	2:42

VOR-A

NE-3, 04 SEP 2025 to 02 OCT 2025

NE-3, 04 SEP 2025 to 02 OCT 2025