

WAAS CH 70418 W05A	APP CRS 047°	Rwy Idg TDZE Apt Elev	5500 309 333
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 5


WATERVILLE RGNL (WVL)

⚠ Inop table does not apply to LPV. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using Augusta altimeter setting. When local altimeter setting not received, use Augusta altimeter setting; increase LPV DA to 544 feet, LNAV/VNAV DA to 623 feet and all visibilities ¾ SM; increase all MDAs 40 feet and Circling Cat C visibility ¾ SM. Night Landing: Rwy 14 NA. For inop MALSF, increase LNAV/VNAV Cat D visibility to 1 mile and LNAV Cats C/D visibility to ¾ mile. For inop MALSF, when using Augusta altimeter setting, increase LPV all Cats visibility to ¾ mile, LNAV/VNAV Cat D visibility to 1 ½ mile, and LNAV Cat D visibility to 1 mile.

MALSF


MISSED APPROACH:
Climb to 1000 then
climbing right turn to
3000 direct PEYSI
and hold.

AWOS-3PT 118.375	PORTLAND APP CON ★ 128.35 299.2	CLNC DEL 124.6 299.2	UNICOM 122.7 (CTAF) 0
----------------------------	---	--------------------------------	---------------------------------



ELEV 333	TDZE 309
----------	----------

4 NM Holding Pattern		PEYSI	CVLRY	EKLAY 1.9 NM to RW05	PEYSI
3000 ← 226°		046° →	1900	*0.9 NM to RW05	*LNAV only.
GP 3.00° TCH 48		046° →	*920	RW05	
		6.8 NM	3.1 NM	1 NM	0.9 NM
CATEGORY	A	B	C	D	
LPV DA		509-¾	200 (200-¾)		
LNAV/VNAV DA		588-¾	279 (300-¾)		
LNAV MDA		620-¾	311 (300-¾)		
CIRCLING	860-1	527 (600-1)	1100-2¼ 767 (800-2¼)	1120-2½ 787 (800-2½)	



NE-1, 04 SEP 2025 to 02 OCT 2025

NE-1, 04 SEP 2025 to 02 OCT 2025