

LOC I-JAN 110.5	APP CRS 159°	Rwy Ldg TDZE Apt Elev 8500 312 346
---------------------------	------------------------	--

ILS or LOC RWY 16L

JACKSON-MEDGAR WILEY EVERS INTL (JAN)

DME or RADAR required for Cat E.

⚠

Circling NA for Cat E southwest of Rwy 16R-34L. When local altimeter setting not received, use HKS altimeter setting and increase S-ILS 16L DA to 531 feet; increase all MDAs 20 feet and S-LOC 16L visibility Cat C/D/E to RVR 3500.

ASR

For inop ALS, increase S-ILS 16L Cat E visibility to RVR 4000 and increase S-LOC 16L Cats C/D/E visibility to RVR 5500. For inop ALS when using HKS Field altimeter setting, increase S-ILS 16L Cat E visibility to RVR 4000 and increase S-LOC 16L Cats C/D/E visibility to RVR 5500.

ALSIF-2

ⓘ

MISSED APPROACH:

Climb to 800 then climbing left turn to 3000 on heading 090° and on MHZ VORTAC R-134 to RAKIN INT/16.5 DME and hold, continue climb-in-hold to 3000.

ATIS 121.05	JACKSON APP CON ★ 123.9 317.7	JACKSON TOWER ★ 120.9 (CTAF) 352.0	GND CON 121.7 348.6	UNICOM 122.95
-----------------------	---	--	-------------------------------	-------------------------

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71). Remain within 10 NM

800

3000

hdg 090°

RAKIN

2200

339°

159°

2200

2200

1340

2.7 NM

3.1 NM

GS 3.00° TCH 55

HARAG INT MHZ 1.5

HIGPU INT MHZ 3.5

CATEGORY	A	B	C	D	E
S-ILS 16L	512/18 200 (200-½)				
S-LOC 16L	660/24	348 (400-½)	660/30	348 (400-¾)	
CIRCLING	880-1 534 (600-1)	900-1 554 (600-1)	900-1½ 554 (600-1½)	960-2 614 (700-2)	1040-2½ 694 (700-2½)

FAF to MAP 5.8 NM

Knots	60	90	120	150	180
Min:Sec	5:48	3:52	2:54	2:19	1:56

JACKSON, MISSISSIPPI
Amdt 9 12JUN25

JACKSON-MEDGAR WILEY EVERS INTL (JAN)
32°19'N-90°05'W

ILS or LOC RWY 16L