


WAAS CH 58141	APP CRS 230°	Rwy Idg TDZE 182	5501
W23A		Apt Elev 182	

RNAV (GPS) RWY 23

SUMTER (SMS)

RNP APCH. ⚠ Circling NA to Rwy 14 and 32. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C or above 54°C. Inop table does not apply to LPV all Cats. For inop ALS increase LNAV/VNAV Cat A/B visibility to ¾ SM.		ODALS ⬆ ⋮	MISSED APPROACH: Climb to 600 then climbing left turn to 2400 direct GAUGH and hold.
---	--	--	---

AWOS-3 118.075	SHAW APP CON★ 125.4	UNICOM 122.7 (CTAF) 0
--------------------------	-------------------------------	---------------------------------



ELEV 182 TDZE 182

230°

30°

180°

90°

0°

270°

180°

90°

0°

270°

600

2400

GAUGH

*LNAV only.

WUMIS 2.6 NM to RW23

AGOZE 1900

GAUGH 4 NM Holding Pattern

050° → 6000

← 230° 2400

GP 3.00° TCH 44

CATEGORY	A	B	C	D
LPV DA	382-¾ 200 (200-¾)			
LNAV/VNAV DA	460-¾ 278 (300-¾)			
LNAV MDA	540-¾ 358 (400-¾)	540-⅞ 358 (400-⅞)		
CIRCLING	600-1 418 (500-1)	680-1 498 (500-1)	1000-2½ 818 (900-2½)	1000-2¾ 818 (900-2¾)