

NDB AIK

347

APP CRS

225°

Rwy Ldg

5500

TDZE

515

Apt Elev

529

NDB RWY 25

AIKEN RGNL (AIK)

▼

NA

When local altimeter setting not received, use Augusta Rgnl at Bush Fld altimeter setting and increase all MDAs 120 feet; increase S-25 Cats B/C/D and Circling Cat C visibility ¼ SM. For inop ODALS, increase S-25 Cat C/D visibility to 1⅞ mile. For inop ODALS when using Augusta Rgnl at Bush Fld altimeter setting, increase S-25 Cat C/D visibility to 2½ mile. Helicopter visibility reduction below ¾ SM NA.

ODALS

MISSED APPROACH: Climbing right turn to 2200 in AIK NDB holding pattern.

AWOS-3PT 118.025	AUGUSTA APP CON ★ 119.15 284.625	CLNC DEL 126.075	UNICOM 122.8 (CTAF) 0
---------------------	-------------------------------------	---------------------	--------------------------

COLLIERS 113.9 IRQ Chan 86

COLUMBIA 114.7 CAE Chan 94

2400 102° (24.5)

225° 180° 360° 045°

738 548

IAF AIKEN 347 AIK

A 1107

2200 251° (33.5)

MSA AIK 25 NM 3000

A 1906

2200 AIK

AIK NDB

Remain within 10 NM

045° 2200 225°

CATEGORY	A	B	C	D
S-25	1180-3/4 665 (700-3/4)	1180-13/4 665 (700-13/4)	1180-13/4 651 (700-13/4)	1420-3 891 (900-3)
CIRCLING	1180-1 651 (700-1)			

ELEV 529

TDZE 515

REIL Rwy 25

MIRL Rwy 7-25 0

AIKEN, SOUTH CAROLINA

Amdt 10E 30DEC21

33°39'N-81°41'W

AIKEN RGNL (AIK)

NDB RWY 25