


WAAS CH 61300 W30A	APP CRS 296°	Rwy Idg TDZE 619 Apt Elev 632	5500
--	------------------------	---	-------------

RNAV (GPS) RWY 30


BUTLER COUNTY RGNL/HOGAN FLD (HAO)

RNP APCH - GPS.			MALS	MISSED APPROACH: Climb to 2700 direct MONTR and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. Inop table does not apply to LPV.				

ASOS 121.425	CINCINNATI APP CON 121.0 254.25	CLNC DEL 126.25	UNICOM 123.05 (CTAF) 0
------------------------	---	---------------------------	----------------------------------



ELEV 632	TDZE 619
-----------------	-----------------



2700 MONTR		4 NM Holding Pattern			
RW30		PUNUE 3.3 NM to RW30		HOLGR 2600	
1.3 NM to RW30		296°		297°	
1700		2600		117° → 6000 ← 297° 3000	
GP 3.00° TCH 46					
1.3		2 NM		2.8 NM	
8.1 NM					
CATEGORY	A		B	C	D
LPV DA	819-3/4 200 (200-3/4)				
LNAV/ VNAV DA	1080-1 1/8 461 (500-1 1/8)				
LNAV MDA	1080-3/4 461 (500-3/4)			1080-1 1/8 461 (500-1 1/8)	
CIRCLING	1280-1 648 (700-1)			1300-1 3/4 668 (700-1 3/4) 1760-3 1128 (1200-3)	