


Baro-VNAV NA when using Somerset altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Somerset altimeter setting: increase all DA 89 feet and all MDA 100 feet; increase LPV all Cats visibility ¼ mile, increase LNAV/VNAV all Cats visibility ⅓ mile, increase LNAV Cats C and D visibility ¼ mile, and increase Circling Cats C visibility ¼ mile and Cat D visibility ½ mile. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 3000 direct KANOA and hold.

AWOS-3 121.125	INDIANAPOLIS CENTER 124.625 353.65	UNICOM 122.7 (CTAF) 0
-------------------	---------------------------------------	--------------------------



3000	KANOA	VGSI and RNAV glidepath not coincident (VGSI Angle 3.25/TCH 40).				4 NM
		PALSE 2.7 NM to RW23	BOCVA 2500	DOODA	Holding Pattern	
*LNAV only.			2500	055°	3000	
		RW23	*1820	235°		GP 3.00° TCH 48
		2.7 NM	2.1 NM	6.9 NM		
CATEGORY	A	B	C	D		
LPV DA		1177-¾	256 (300-¾)			
LNAV/VNAV DA		1366-1½	445 (500-1½)			
LNAV MDA	1360-1	439 (500-1)	1360-1¼	439 (500-1¼)		
CIRCLING	1380-1 459 (500-1)	1400-1 479 (500-1)	1480-1½ 559 (600-1½)	1660-2¼ 739 (800-2¼)		

