



VORTAC CEW 115.9 Chan 106	APP CRS 106°	Rwy Idg TDZE Apt Elev N/A N/A 214
---	------------------------	---

VOR-A

BOB SIKES(CEW)

▼ ▲ Circling NA for Cat D west of Rwy 17-35. When local altimeter setting not received, use Eglin AFB altimeter setting and increase all MDA 60 feet and increase Circling Cat C/D visibility ¼ SM.	ASOS 119.275	EGLIN APP CON 124.05 284.65	UNICOM 123.075 (CTAF) 0
--	---	--	--



One Minute Holding Pattern		CEW VORTAC		1200 ↑	2200 ↷	CEW 
<u>6000</u> ← 286° <u>2200</u> → 106°		* 106°		NOTME CEW <u>7.3</u>	MADEW CEW <u>8.3</u>	
* 960 when using Eglin AFB altimeter setting.		7.3 NM		* 900	1 NM	
CATEGORY	A	B	C	D		
 CIRCLING	900-1	686 (700-1)	900-2 686 (700-2)	900-2¼ 686 (700-2¼)		
NOTME FIX MINIMUMS (ADF OR DME REQUIRED)						
 CIRCLING	700-1	486 (500-1)	820-1¾ 606 (700-1¾)	840-2 626 (700-2)		