

LOC I-OUF 111.5	APP CRS 274°	Rwy Ldg TDZE Apt Elev 6500 778 778
---------------------------	------------------------	--

ILS or LOC RWY 27
ELKHART MUNI (EKM)

RNP APCH - GPS.

RADAR required for procedure entry.

▼

▲

Circling NA to Rwy 8 and 26. Rwy 27 helicopter visibility reduction below RVR 4000 NA. Circling Rwy 18 and 36 NA at night. When local altimeter setting not received, use SBN altimeter setting and increase S-ILS 27 DA to 1100 feet, increase all MDAs 40 feet, and S-LOC 27 visibility Cat C/D to RVR 5500, and Circling visibility Cat D ¼ SM. For inop ALS, increase S-ILS 27 all Cats visibility to RVR 4500 and S-LOC 27 Cat A/B visibility to 5500 and Cat C/D visibility to 1 ½ SM. For inop ALS when using SBN, increase S-LOC 27 Cat A/B visibility to RVR 5500, and Cat C/D visibility to 1 ½ SM.


MALSR

MISSED APPROACH:
Climb to 1500 then climbing right turn to 4000 direct JJANN and hold.

AWOS-3 124.475	SOUTH BEND APP CON ★ 118.55 257.8	ELKHART TOWER ★ 119.5 (CTAF) 0	GND CON 121.8	CLNC DEL 121.8	CLNC DEL 119.7 (When twr closed)	UNICOM 122.95
--------------------------	---	--	-------------------------	--------------------------	---	-------------------------

MISSED APCH FIX

MSA EKM 25 NM



1500

4000

JJANN

RECKV OM

AYUYI GU

One Minute Holding Pattern

2177

2300

5200

2500

GS 3.00°

TCH 46

4.2 NM

5.6 NM

CATEGORY	A	B	C	D
S-ILS 27		1066/40	288 (300-¾)	
S-LOC 27	1240/40	462 (500-¾)	1240/50	462 (500-1)
▲ CIRCLING	1240-1 462 (500-1)	1300-1 522 (600-1)	1380-1¾ 602 (700-1¾)	1580-2½ 802 (900-2½)

ELEV 778 D TDZE 778

MIRL Rwy 18-36
HIRL Rwy 9-27
REIL Rwys 9, 18 and 36

FAF to MAP 4.2 NM

Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24

EC-2, 04 SEP 2025 to 02 OCT 2025

EC-2, 04 SEP 2025 to 02 OCT 2025