

WAAS CH 78232 W19A	APP CRS 190°	Rwy Idg TDZE Apt Elev	5010 979 979
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 19

BARABOO/WISCONSIN DELLS RGNL (DLL)



RNP APCH.

⚠

Circling NA to Rwy 14 and 32.
Rwy 19 helicopter visibility reduction below ¾ SM NA.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.

MISSED APPROACH:
Climb to 3000 direct
TRVIS and hold.

AWOS-3 118.325	MADISON APP CON ★ 135.45 343.7	UNICOM 123.05 (CTAF) 0
--------------------------	--	----------------------------------



3000 TRVIS		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 32)				4 NM
* LNAV only.		TECYO 2.5 NM to RW19	KRUBI 2900	ZAVOX	011° → 6000	Holding Pattern
* 1.3 NM to RW19		* 1800	190°	191°	← 191°	3000
→ 1.3 NM		→ 1.2 NM	→ 3.4 NM	→ 6 NM	GP 3.00° TCH 53	
CATEGORY	A	B	C	D		
LPV DA	1341-1		362 (400-1)		NA	
LNAV/VNAV DA	1302-1		323 (400-1)		NA	
LNAV MDA	1420-1	441 (500-1)	1420-1⅜ 441 (500-1⅜)		NA	
CIRCLING	1520-1	541 (600-1)	1580-1¾ 601 (700-1¾)		NA	

EC-3, 04 SEP 2025 to 02 OCT 2025

EC-3, 04 SEP 2025 to 02 OCT 2025