

LOC/DME I-UZA
108.5
Chan **22**

APP CRS
016°

Rwy Idg **5500**
TDZE **666**
Apt Elev **666**

ILS Z or LOC Z RWY 2

ROCK HILL/YORK COUNTY/BRYANT FLD (UZA)

ADF or DME required. VDP NA with Charlotte/Douglas Intl altimeter setting. When local altimeter setting not received, use Charlotte/Douglas Intl altimeter setting and increase all DA 45 feet and all MDA 60 feet. Increase S-LOC 2 Cat C/D visibility ¼ mile. For inop MALSRL, increase S-LOC 2 Cat C/D visibility to 1½ mile. For inop MALSRL, when using Charlotte/Douglas Intl altimeter setting, increase S-LOC 2 Cat C/D visibility to 1½ mile.

NA

MALSRL

MISSED APPROACH: Climb to 1500 then climbing left turn to 3000 on heading 174° and CLT VOR/DME R-203 to CONEL/I-UZA 12.7 DME/RADAR and hold.

ASOS 120.775	CHARLOTTE APP CON 120.05 307.8	GCO 121.725	UNICOM 123.05 (CTAF) 1
------------------------	--	-----------------------	---

DME or RADAR REQUIRED

1037A

1020

802

3000

203

25.1

841

203

2500

016°

6.1

196°

196°

196°

1 min

016°

196°

196°

LOCALIZER 108.5

I-UZA

Chan 22

CHARLOTTE

115.0 CLT

Chan 97

LOM RALLY

227 UZ

I-UZA

A1289

MSA UZ 25 NM

3800

ALTERNATE MISSED APCH FIX

RALLY

UZ

227

I-UZA

6.6

One Minute Holding Pattern

CONEL I-UZA 12.7 RADAR

3000

196°

016°

016°

GS 3.00° TCH 41

2493

2500

6.1 NM

4.3 NM

1.2

RALLY LOM I-UZA 6.6

1500

3000

hdg 174°

CLT R-203

CONEL I-UZA 12.7 RADAR

*LOC only.

*I-UZA 2.3

I-UZA 1.1

CATEGORY	A	B	C	D
S-ILS 2	866-½		200 (200-½)	
S-LOC 2	1080-½	414 (500-½)	1080-¾	414 (500-¾)
CIRCLING	1140-1 474 (500-1)	1160-1 494 (500-1)	1340-2 674 (700-2)	1340-2¼ 674 (700-2¼)

ELEV 666

TDZE 666

02

5500 X 100

016°

MIRL Rwy 2-20

FAF to MAP 5.5 NM

Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

ROCK HILL, SOUTH CAROLINA

Amtd 3 13NOV14

ROCK HILL/YORK COUNTY/BRYANT FLD (UZA)

34°59'N-81°03'W

ILS Z or LOC Z RWY 2