


WAAS CH 69601 W13A	APP CRS 132°	Rwy Idg 5002 TDZE 962 Apt Elev 962
--	------------------------	---

RNAV (GPS) RWY 13

LIVINGSTON COUNTY SPENCER J HARDY (OZW)

RNP APCH.	MALSR	MISSED APPROACH: Climb to 2800 direct BROVI and hold.
 For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.6°C or above 37°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM.		

AWOS-3 118.875	DETROIT APP CON 132.35 284.0	CLNC DEL 121.725 (GCO)	UNICOM 123.0 (CTAF) 0
--------------------------	--	----------------------------------	---------------------------------



4 NM

Holding Pattern

HUCCY

2800

BROVI

6000

3000

312°

132°

GP 3.00°

TCH 48

2500

DURGY

2500

JIVEX

2.1 NM to RW13

*0.9 NM to RW13

*LNAV only

*1660

5.6 NM

2.6 NM

1.2

0.9

CATEGORY	A	B	C	D
LPV DA	1162-½		200 (200-½)	
LNAV/VNAV DA	1212-½		250 (300-½)	
LNAV MDA	1300-½		338 (400-½)	
CIRCLING	1400-1 438 (500-1)	1420-1 458 (500-1)	1600-1¾ 638 (700-1¾)	1600-2 638 (700-2)

132°

132°

132°

5002 X 100

0.4% UP

HIRL Rwy 13-31

REIL Rwy 31