

LOC/DME I-FGH

109.35

APP CRS

041°

Rwy Idg

4775

TDZE

58

Chan

30 (Y)

Apt Elev

72

ILS or LOC RWY 4

EASTON/NEWNAM FLD (ESN)

RADAR and DME required for procedure entry. DME required for LOC only.

▼

▲

Circling Rwy 15, 33 NA at night. Autopilot coupled approach NA below 1000.

MISSED APPROACH: Climb to 2000 on heading 041° and on ATR VOR/DME R-283 to ORETE INT/ATR 31.6 DME and hold.

ATIS	POTOMAC APP CON	EASTON TOWER ★	GND CON	CLNC DEL
124.475	133.75 254.35	118.525 (CTAF) 0	119.075	119.075

One Minute Holding Pattern

GS unusable below 600.

2000

ATR R-283

ORETE

RIKME I-FGH 11.8

WEGRO I-FGH 5.8

hdg 041°

*LOC only

4600 ← 221°

2000 → 041°

GS 3.00° TCH 44

1600

3.4 NM

1.4 NM

CATEGORY	A	B	C	D
S-ILS 4		600-1 ⁵ / ₈	542 (600-1 ⁵ / ₈)	
S-LOC 4	540-1	482 (500-1)	540-1 ³ / ₈	482 (500-1 ³ / ₈)
CIRCLING	540-1 468 (500-1)	640-1 568 (600-1)	640-1 ¹ / ₂ 568 (600-1 ¹ / ₂)	740-2 ¹ / ₄ 668 (700-2 ¹ / ₄)

ELEV 72

D

TDZE 58

TWR

33

0.5% UP

4000 X 100

5500 X 100

0.7% UP

HIRL Rwy 4-22 0

REIL Rws 15, 22 and 33 0

MIRL Rws 15-33 0

EASTON, MARYLAND

Amdt 2D 08SEP22

38°48'N-76°04'W

EASTON/NEWNAM FLD (ESN)

ILS or LOC RWY 4