

APP CRS
108°

Rwy Idg
5001

TDZE
790

Apt Elev
790

RNAV (GPS) RWY 11

FULTON COUNTY (R/C/R)

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Goshen altimeter setting: increase all MDA 100 feet and visibility LNAV Cats C and D and Circling Cats C and D ¼ SM.

MISSED APPROACH: Climb to 3000 direct LOWTO and hold.

AWOS-3
118.775

SOUTH BEND APP CON ★
132.05 257.8

UNICOM
122.7 (CTAF) 0

The main chart displays the RNAV route for RWY 11. Key waypoints and data include:

- KOMECE**: (IF/IAF) KOMECE, 3000 NoPT, 1018°/198° heading, 30 NM to KOMECE (NoPT).
- LIMEY**: (IAF) LIMEY, 3000, 198°/288° heading, 30 NM to LIMEY.
- AFAGU**: (FAF) AFAGU, 2500 (6.1), 108° heading, 2.4 NM to RW11.
- VOYUP**: 965, 1163 A, 946, 873, 1106, 2.4 NM to RW11.
- ISOSY**: (IAF) ISOSY, 3000 NoPT, 1018°/288° heading, 30 NM to ISOSY.
- ISOSY**: 3000, 018°/288° heading, 30 NM to ISOSY.
- LOWTO**: 4 NM, 108°/288° heading.

ELEV 790

TDZE 790

4 NM Holding Pattern

VGSI and descent angles not coincident (VGSI Angle 3.50/TCH 50).

3000 LOWTO

108°

288°

5001 X 75

29

108°

288°

1600

2500

3.05° TCH 45

2.4 NM to RW11

6.1 NM

2.8 NM

2.4 NM

CATEGORY	A	B	C	D
LNAV MDA	1220-1	430 (500-1)	1220-1¼ 430 (500-1¼)	1220-1½ 430 (500-1½)
CIRCLING	1280-1 490 (500-1)	1360-1 570 (600-1)	1480-2 690 (700-2)	1620-2¾ 830 (900-2¾)

REIL Rwy 11 and 29 0

MIRL Rwy 11-29 0

ROCHESTER, INDIANA

Amtd 1A 02DEC21

41°04'N-86°11'W

FULTON COUNTY (R/C/R)

RNAV (GPS) RWY 11