

WAAS CH 49032 W14A	APP CRS 142°	Rwy Idg TDZE Apt Elev	4899 1132 1136
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 14

MORRIS MUNI/CHARLIE SCHMIDT FLD (MOX)


RNP APCH-GPS.

▼

Baro-VNAV and VDP NA when using BBB altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use BBB altimeter setting and increase LPV and LNAV/VNAV DA to 1440 feet. Increase all MDAs 60 feet and visibility LNAV Cat C ½ SM and visibility Circling Cat C ¼ SM.

MISSED APPROACH: Climb to 3500 direct EXJUP and hold.

AWOS-3PT 118.6	MINNEAPOLIS CENTER 126.1 269.2	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 1136 TDZE 1132

HIRL Rwy 14-32 0
REIL Rwy 14 and 32 0

	ZITOG	EBYEX	YOPCU	EXJUP
	4 NM Holding Pattern	3000	2 NM to RW14	3500
	6000 ← 322°	142° →	1800	
	3000	3000	1 NM to RW14	
	GP 3.00°			
	TCH 40			
	8 NM	3.8 NM	1 NM	1 NM
CATEGORY	A	B	C	D
LPV DA	1382-1	250 (300-1)		NA
LNAV/VNAV DA	1382-1	250 (300-1)		NA
LNAV MDA	1480-1	348 (400-1)		NA
CIRCLING	1560-1 424 (500-1)	1600-1 464 (500-1)	1860-2 724 (800-2)	NA