

WAAS CH 90236 W26A	APP CRS 257°	Rwy ldg TDZE Apt Elev	5002 20 23
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 26



JENNINGS (3R7)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F).
DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Lake Charles Rgnl altimeter setting.

▲ Night landing: Rwy 8, 31 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Lake Charles Rgnl altimeter setting: Increase all DA 69 ft and all MDA 80 ft; increase LPV and LNAV/VNAV all Cats visibility ¼ mile, increase LNAV/Circling Cat C visibility ½ mile.

MISSED APPROACH: Climb to 3000 direct CEGUV and hold.

AWOS-3PT 121.150	LAKE CHARLES APP CON ★ 119.8 282.3	UNICOM 122.8 (CTAF) 0
----------------------------	--	--



3000 CEGUV		TUYOD		4 NM Holding Pattern
*LNAV only.		WADBO 1.6 NM to RW26	MALMS 1700	077° → 3000
RW26		*1 NM to RW26	*580	← 257°
1 NM		0.6 NM	3.5 NM	6.5 NM
CATEGORY	A	B	C	D
LPV DA	290-7/8 270 (300-7/8)			NA
LNAV/VNAV DA	300-7/8 280 (300-7/8)			NA
LNAV MDA	400-1 380 (400-1)			NA
CIRCLING	580-1 557 (600-1)		680-13/4 657 (700-13/4)	NA

GP 3.00° TCH 50