


WAAS CH 61225 W32A	APP CRS 316°	Rwy Idg TDZE 4176 Apt Elev 4176
--	------------------------	---

RNAV (GPS) RWY 32

MONDELL FLD (ECS)

RNP APCH. ⚠ When Newcastle altimeter setting not received, procedure NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -23°C (-9°F) or above 53°C (128°F). Circling NA northeast of Rwy 14-32. For inop ODAL, increase LNAV/VNAV visibility all Cats and LNAV Cats C/D ½ mile. Inop table does not apply to LPV all Cats and LNAV Cats A/B.	ODALS 	MISSED APPROACH: Climb to 9500 direct PULVE and hold, continue climb-in-hold to 9500.
--	-----------	---

AWOS-3PT 118.0	DENVER CENTER 127.95 338.2	UNICOM 122.8 (CTAF)
--------------------------	--------------------------------------	-------------------------------



ELEV 4176	TDZE 4176				
*LNAV only.					
CATEGORY	A	B	C	D	
LPV DA	4385-1 209 (300-1)				
LNAV/VNAV DA	4618-1½ 442 (500-1½)				
LNAV MDA	4600-1 424 (500-1)		4600-1½ 424 (500-1½)		
CIRCLING	4700-1 524 (600-1)		4720-1½ 544 (600-1½)		5000-2¾ 824 (900-2¾)