

WAAS	APP CRS	Rwy Idg	3693
CH 66043	055°	TDZE	435
W06A		Apt Elev	435

RNAV (GPS) RWY 6

NEW GARDEN (N57)

RNP APCH.

V

NA

VDP NA when using New Castle altimeter setting. Obtain local altimeter setting on CTAF; when local altimeter setting not received, use New Castle altimeter setting and increase all MDA 80 feet. Increase LP Cat C visibility 3/8 SM, LNAV Cat C visibility 1/4 SM and Circling Cat C visibility 1/2 SM.

MISSED APPROACH:
Climb to 2200 direct ZEYNU and hold.

PHILADELPHIA APP CON	CLNC DEL	UNICOM
124.35 319.15	125.6	123.05 (CTAF) 0

ELEV 435	TDZE 435
----------	----------

4 NM Holding Pattern

DELFAYOSGUYOSGU

20001240

5 NM2.4 NM1.4 NM1 NM

2200

ZEYNU

CATEGORY	A	B	C	D
LP MDA	800-1 365 (400-1)			NA
LNAV MDA	820-1	385 (400-1)	820-1 385 (400-1 1/8)	NA
CIRCLING	960-1	525 (600-1)	960-1 525 (600-1 1/2)	NA

MIRL Rwy 6-24 0