

LOC I-PXE <u>109.15</u>	APP CRS 005°	Rwy Idg TDZE Apt Elev	5004 417 418
-----------------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 36
PERRY-HOUSTON COUNTY (PXE)

	DME or RADAR required
--	-----------------------


T Autopilot coupled approach NA below 900. Rwy 36 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Inop table does not apply to S-LS-36. When local altimeter setting not received, use Middle Georgia Rgnl altimeter setting: increase all DA to 705 feet; increase all MDAs 40 feet and Circling visibility Cats C and D $\frac{1}{4}$ SM. For inop ALS, increase S-LOC 36 Cats A/B visibility to 1 SM and Cats C/D to $\frac{1}{2}$ SM. For inop ALS when using Middle Georgia Rgnl altimeter setting, increase S-LS all Cats visibility to $\frac{3}{4}$ SM and S-LOC 36 Cats A/B visibility to 1 SM.

MALSR


MISSED APPROACH: Climb to 1100 then climbing left turn to 2300 on heading 195° and VNA R-291 to SCTRY INT/ RADAR and hold.

AWOS-3
123.825

ATLANTA APP CON★
124.2 279.6

UNICOM
122.725 (CTAF) **L**

FIFV 418		TDZE 417
----------	--	----------



1100 2300 VNA R-291 SCTR INT VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 30). One Minute Holding Pattern

hdg 195°

PRDUE INT RADAR 2100 SCTR INT RADAR 185° 005° 4000 2300

5.2 NM 6.7 NM GS 3.00° TCH 45

CATEGORY	A	B	C	D
S-ILS 36	667- ³ / ₄ 250 (300- ³ / ₄)			
S-LOC 36	900- ³ / ₄ 483 (500- ³ / ₄)		900-1 483 (500-1)	
 CIRCLING	900-1 482 (500-1)		1140-2 722 (800-2)	1280-2 ³ / ₄ 862 (900-2 ³ / ₄)