



WAAS CH 77824 W05A	APP CRS 050°	Rwy Idg TDZE Apt Elev 468	6011 468 468
--	------------------------	--	---

RNAV (GPS) RWY 5
JIMMY CARTER RGNL (ACJ)

RNP APCH. Baro-VNAV NA when using Columbus altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 40°C. Rwy 5 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Columbus altimeter setting and increase LPV DA to 832 feet and visibility ¼ SM, LNAV/VNAV DA to 954 feet and visibility ⅓ SM, increase all MDAs 120 feet and LNAV Cats C/D visibility ⅓ SM, and Circling Cat C visibility ½ SM, Cat D ¼ SM. Circling Rwy 10, 28 NA at night.	MISSED APPROACH: Climb to 2600 direct HASER and hold.
--	--

AWOS-3 128.375	ATLANTA APP CON ★ 124.2 323.1	CLNC DEL 119.95	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------	---------------------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 58).		2600 HASER	
2600 ← 230°		050° →		*LNAV only.	
GP 3.00° TCH 45		2200		RW05	
5.7 NM		3.4 NM		1.9 NM	
CATEGORY	A	B	C	D	
LPV DA		718-1	250 (300-1)		
LNAV/VNAV DA		840-1	372 (400-1)		
LNAV MDA		840-1	372 (400-1)		
CIRCLING	940-1	472 (500-1)	1020-1½ 552 (600-1½)	1280-2¾ 812 (900-2¾)	